



ACRYLPACK-S

ACRYLIC SEALER COLOR PACK TECHNICAL DATA & APPLICATION INSTRUCTION

PRODUCT DESCRIPTION

Acrylpack-S is a high solids, concentrated, solvent based acrylic tint system specially formulated for solvent based acrylic sealers. Acrylpack-S is formulated with high quality, ultra fine particle pigments that easily disperses in solvent based acrylic sealers. Acrylpack-S is a superior choice to obtain a semi-transparent stain or a solid opaque colored finish in most solvent based acrylic sealers

BENEFITS/FEATURES

- Easy way to create a beautiful, solid color concrete surface
- Economical
- Easily disperses into most solvent based acrylic sealers
- Available in 14 standard colors

RECOMMENDED APPLICATIONS

- Driveways
- Patios
- Sidewalks
- Discolored Concrete
- Many other concrete surfaces where a solid color sealing and dust proofing method is desired.
- Use with Regal Gloss, Kingdom Guard or Kingdom Guard Plus

TECHNICAL INFORMATION

Drying Time.....	Refer to Sealer Tech Data	Wet Appearance.....	varies
Re-Coat Time.....	Refer to Sealer Tech Data	Dry Appearance.....	Tinted & Medium/High Gloss
Foot Traffic.....	Refer to Sealer Tech Data	Application Temp.....	50°F - 80°F
Wheel Traffic.....	Refer to Sealer Tech Data		

APPROXIMATE COVERAGE RATES

Semi-Transparent	2 - 8 ounces per gallon	8 - 16 ounces per 5 gallon
Solid Opaque Finish	8 ounces per gallon	32 ounces per 5 gallon

**Coverage rates above reflect approximate coverage of finished product (per gallon) applied per instructions. Coverage rates will vary significantly & will be determined upon the surface porosity of the concrete as well as the application style.*

PACKAGING & SHELF LIFE

Acrylpacks are available in 1 quart containers. Up to one year from manufacture date in its original, unopened container stored at room temperature.

CLEAN-UP & PRODUCT REMOVAL

Use Xylene. Dispose of containers in accordance with local, state and federal regulations. Refer to Sealer Technical Data Sheet (TDS) for further instruction.

SURFACE PREPARATION: Concrete surface must be clean and free of all contaminants and water. Do not apply if rain is forecast within 24 hours. If moisture is present or if the surface is not clean and free of all contaminants, the sealer may have white spots and have premature delamination and failure.

MIXING: Mix desired amount in a solvent based acrylic sealer for 1-2 minutes using a squirrel mixer prior to application. Allow any foam to settle prior to use. Re-mix as needed.

APPLICATION: Review the Technical Data Sheet (TDS) and SDS for the chosen solvent based acrylic sealer prior to use.

CAUTION: Do not add too much color! Apply a test area prior to job application for desired appearance. Over pigmentation may cause color float or streaking, especially in the darker colors! Do not allow to puddle! The average usage is 1 quart (32 oz.) per 5 gallons of material for most opaque applications. For lighter colors it may take more and darker colors may take less depending on the application as well as the composition of the solvent based acrylic sealer.

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. When applying, do not exceed 400 sq. ft. per gallon. Applying too thin of a coating may cause inadequate film formation or performance expectations may be limited. **DO NOT USE ON BRICK.**

Substrate and air temperature must be no less than 50°F and not exceed 80°F. If applied outside these limits the sealer may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing. Note that in direct sunlight, substrate temperature can exceed 150°F which can cause extreme bubbling issues.

PRECAUTIONS & LIMITATIONS

- This product will not freeze during storage, however, allow temperature to rise to 50°F prior to application.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- If using indoor, use proper ventilation while applying and for hours after application to ensure fumes are removed.
- It is not recommended to apply product over carpet, tile, or other types of floor adhesives.
- This product performs best when applied as one or two medium-light coats, not one heavy coat.
- Please be aware that this product when cured may be slippery when wet. An anti-slip additive, such as Sure-Grip, can be added to reduce slip hazards.
- This product is not resistant to brake fluid, gasoline, and many similar products.
- It is not recommended to thin product. Improper thinning may cause sealer to delaminate in a short time frame.
- This product may darken the surface of many new and existing concrete slabs. Test prior to use.
- Follow the instructions for the solvent based acrylic sealer that is to be used for application guidelines.
- Solvent vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition source locations distant from material handling point.

SPECIAL NOTES

Please consult Safety Data Sheet (SDS), Technical Data Sheet (TDS) & read Warranty information prior to use.
FOR PROFESSIONAL USE ONLY!