



KINGDOM CURE

SLOW-DRYING, UV RESISTANT, CURING & SEALING COMPOUND TECHNICAL DATA & APPLICATION INSTRUCTION

PRODUCT DESCRIPTION

Kingdom Cure 1315 is a slow-drying, VOC compliant, UV resistant, Low Viscosity 25% solids, solvent based curing and sealing compound as well as a dust-proofer for concrete surfaces. **Kingdom Cure** offers improved resistance to rain, sun, freezing temperatures, stains and other pollutants that sometimes can be hazardous to concrete. **Kingdom Cure** forms a superior moisture retentive film on freshly placed concrete and provides excellent protection & color enhancement for decorative concrete. **Kingdom Cure's** slow-dry formula is perfect for high temperature regions or to combat sealer issues during seasonal high temperatures.

BENEFITS/FEATURES

- Can be used as a means of dustproofing most decorative concrete surfaces
- Its low viscosity formula makes this product very easy to spray
- Rolls out smooth with no roller streaks
- UV resistant
- Slow Dry
- High Gloss
- Low Cost

RECOMMENDED APPLICATIONS

Kingdom Cure is recommended for both interior and exterior freshly placed, finished decorative concrete where a high gloss solvent based curing and sealing compound is specified. Not recommended for standard concrete.

APPROXIMATE COVERAGE RATES

Application Surface	First Coat	Second Coat
Fresh Concrete (green-same day)	200-250 sq ft/gallon	<i>not recommended</i>
Cured Decorative Concrete	200-250 sq ft/gallon	300-350 sq ft/gallon
Cured Standard Concrete	<i>not recommended</i>	<i>not recommended</i>

*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided.

TECHNICAL INFORMATION

Solids.....25%	Wet Appearance.....Clear
Drying Time.....1 - 2 hours	Dry Appearance.....Clear with High Gloss
Re-Coat Time.....4 - 24 hours	VOC Content.....<350 g/l
Foot Traffic.....4 - 6 hours	Blush Resistance.....Superior
Wheel Traffic.....24 - 48 hours	Solvent Resistance.....Minimal
Full Cure.....7 Days	Concrete Adhesion.....Excellent
	Application Temp.....40°F - 85°F

**Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

ASTM C 309, Type 1, Class A & B, *ASTM C 1315, Type 1, Class A, AASHTO Specification M-148, Type 1, Class A & B - DRIED COATING IS USDA ACCEPTED - This product complies with federal AIM Rule VOC regulations and with VOC standards in Ohio, Illinois, Maryland, New York, New Jersey, Delaware, Pennsylvania, Maine, New Hampshire, Virginia, and the District of Columbia. *Does not meet Flashpoint requirement for ASTM C 1315

SHELF LIFE

Kingdom Cure has a shelf life of up to two years in it's original, sealed, unopened container.

PACKAGING

Kingdom Cure is packaged in 1 gallon, 5 gallon pails and 55 gallon drums.

SURFACE PREPARATION:

Concrete surface must be clean and DRY and free of all contaminants and water. Do not apply if rain is forecast within 24 hours. If moisture is present or if the surface is not clean and free of all contaminants, the sealer may have white spots and have premature de-lamination and failure. May be applied when damp (not “wet”) to freshly placed concrete surfaces. Substrate temperature must be no less than 40°F and not exceed 80°F. If applied outside these limits the sealer may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing.

MIXING:

Stir well before using. Material may separate during long term storage.

APPLICATION:

Apply using an 3/8” long nap roller cover using long even uniform strokes at approximately 250-400 square feet per gallon depending on porosity and texture of substrate. An airless sprayer containing a .375 tip size may be used as well. Thick or puddle areas may prevent the solvent from evaporating and may be susceptible to moisture intrusion which may cause milky white spots. Applying too thin may cause sealer to prematurely delaminate, flake or wear away. Allow sealer to dry for 24 hours for light traffic and at least 48 hours for heavy traffic. If applying two coats, wait approximately 4 – 6 hours between coats.

PLEASE NOTE:

It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending upon porosity, density, texture etc. If applying by spray method, extended coverage rates may be achieved, but be aware that less material will be applied and inadequate film formation or performance expectations may be limited.

CLEAN-UP

Use Xylene. Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL

Dried, cured sealer may be removed with a commercial paint stripper or by using a diamond grinding method, sandblasting method or similar mechanical action.

PRECAUTIONS AND LIMITATIONS

- **Kingdom Cure** will not freeze during storage, however allow temperature to rise to 50°F prior to application.
- Block all HVAC ventilation ducts prior to application to eliminate distribution of solvent fumes.
- Keep away from open flames. **Kingdom Cure** is flammable and is very susceptible to ignition.
- It is not recommended to apply **Kingdom Cure** over carpet, tile, and other types of floor adhesives.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- **Kingdom Cure** was designed as a cure & seal and to be applied in one light coat.
- Please be aware that this product when cured may be slippery when wet.
- **Kingdom Cure** is not resistant to brake fluid, gasoline, and many similar products.
- It is not recommended to thin **Kingdom Cure**. Improper thinning may cause sealer to delaminate in a short time frame.
- **Kingdom Cure** will darken the surface of many new & existing concrete slabs. Test prior to use.
- **Kingdom Cure** is not designed for use on flatwork. Solvent based sealers will highlight finishing marks in the concrete giving the surface a splotchy appearance.

SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. FOR PROFESSIONAL USE ONLY!